



**DryGuard® enhanced oriented strand board (OSB)** is a multi-layered sub-floor product that has improved moisture resistance throughout the panel plus a black edge seal to help reduce moisture absorption. This means protection from the elements that helps avoid costly and time-consuming joint sanding. Each panel is third-party certified for quality and is rated for Exposure 1 bond durability for protected applications and limited exposure during normal construction delays.

#### Available Sizes (Sized for 4' x 8')

**Square Edge** 3'-11<sup>7</sup>/<sub>8</sub>" (1.216 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m)

**Tongue & Groove** 3'-11<sup>1</sup>/<sub>2</sub>" (1.206 m) x 7'-11<sup>7</sup>/<sub>8</sub>" (2.435 m)

#### Building Code Performance Categories, Panel Thickness

- 19/32 CAT, 0.578" (14.68 mm)
- 23/32 CAT, 0.703" (17.85 mm)

#### Specifications

**Length/Width Tolerance** ±1<sup>1</sup>/<sub>6</sub>" (±1.6 mm)

**Straightness Tolerance** ±1<sup>1</sup>/<sub>6</sub>" (±1.6 mm)

**Squareness Tolerance** ±1<sup>1</sup>/<sub>8</sub>" (±3.2 mm)

**Testing Agency** APA® – The Engineered Wood Association

**Classification** **Exposure 1** – OSB suitable for uses not permanently exposed to the weather. Panels classified as Exposure 1 are intended to resist the effects of moisture on structural performance as may occur due to construction delays, or other conditions of similar severity.

**Code Fire Classification** Class III or C

**Flame Spread Rating** 76-200, smoke-developed index <450

**Building Code Compliance** PS 2-10

#### Other Information

**Forestry Certification** DryGuard OSB panels are made from wood sourced through a system that is third-party certified to the Sustainable Forestry Initiative® procurement standard.



**Product Warranty** DryGuard OSB is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at [buildgpc.com](http://buildgpc.com).

**International Shipping** To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. **Pallets made with engineered wood, including DryGuard® OSB, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing", [www.PerformancePanels.com](http://www.PerformancePanels.com))

**Formaldehyde Emissions** DryGuard OSB contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

#### Manufacturing Locations

Location	APA Mill Number	Zip Code	Harvest Radius
Allendale, SC	531	29827	50 miles
Fordyce, AR	475	71742	100 miles

For installation instructions, specifications and warranty, please visit [buildgpc.com](http://buildgpc.com) | 800-284-5347



DryGuard, Georgia-Pacific and the DryGuard and Georgia-Pacific logos are trademarks owned by or licensed to Georgia-Pacific Wood Products LLC. APA and Sturd-I-Floor are registered trademarks of APA-The Engineered Wood Association. Sustainable Forestry Initiative, SFI, and the SFI logo are trademarks of Sustainable Forestry Initiative, Inc. ©2019 Georgia-Pacific Wood Products LLC. All rights reserved. Lit. Item #621516

Georgia-Pacific 133 Peachtree St., N.E., Atlanta, GA 30303