

**Manufacturer**

Georgia-Pacific Gypsum 133 Peachtree Street Atlanta, GA 30303	Georgia-Pacific Canada 2180 Meadowvale Boulevard, Suite 200 Mississauga, ON L5N 5S3
---	---

Technical Service Hotline: 1-800-225-6119

**Description**

**ToughRock® Shaftliner** panels have a noncombustible gypsum core encased in moisture-resistant green paper facings.

**Primary Uses**

ToughRock Shaftliner panels are one component in gypsum board shaftwall, stairwell, area separation wall, and horizontal membrane and duct protection assemblies with a designated fire-resistive rating used in building construction.

A specially formulated gypsum core enables ToughRock Shaftliner panels as an assembly component, helping to protect framing members while preventing or delaying the spread of fire.

**Limitations**

- Non-load bearing
- Not to be used in an unlined air supply or return duct
- Not designed for exposure to constant high-moisture conditions or direct water
- Elevator door assemblies require support independent of shaftwall partitions
- Good construction practice calls for partition control joints to coincide with those of the building structure
- Limiting loads and heights not to exceed design specification
- Provide flexible sealant/caulk at partition perimeters and penetrations to avoid air leakage/whistling and dust collection

**Applicable Standards: ASTM C1396, Section 6**

Building Code Conformity: ToughRock Shaftliner panels conform to the requirements of major building codes.

**Sizes**

Thickness, nominal	1" (25 mm)
Widths, nominal	24" (610 mm)
Lengths, standard	8' – 12' (2435 mm – 3658 mm)

**Edges**

Double beveled.

**Supplemental Materials**

Metal shaftwall and area separation wall assembly components, corner beads and trim, expansion joints, joint tape, joint compound, sealants.

**Technical Data – Surface Burning Characteristics**

Flame spread 15 and smoke developed 0 when tested according to ASTM E84. The core is noncombustible when tested in accordance with ASTM E136.

**Fire Resistance Ratings**

Toughrock Shaftliner panels are classified for fire resistance by UL. Toughrock Shaftliner is UL classified Type TP-6.

**Sound Control**

Sound-rated assemblies require sealing at top, bottom, intersections, penetrations and other locations where sound leaks may develop.

**Installation – Application Standards**

Application regarding board orientation, fastener type and spacing shall be consistent with the tested construction details.

**Methods**

Appropriate methods of installation are based on the desired fire resistance rating or specified STC value required. These ratings and values require that details of the tested assemblies be followed. In addition to these designs, the installation methods outlined in Gypsum Association Publication GA-216 will facilitate optimum performance through established construction practices.

ToughRock Shaftliner panels are but one component in gypsum board wall assemblies. Other fire-rated gypsum boards as well as certain metal components are used to make an assembly. The gypsum board wall shall be erected with all the components used in the successful fire endurance tests. The installation method selected should be planned carefully to minimize the number of end joints. ToughRock Shaftliner can be cut to the necessary size by scoring the face paper with a sharp knife then snapping away from the cut face. The back paper is then cut or broken by snapping the board in the opposite direction. All cut edges and ends are smoothed by rasping or other suitable methods to form tight-fitting joints when installed.

**Handling and Use – Caution**

This product may contain fiberglass which may cause skin irritation. Dust and fibers produced during the handling and installation of the product may cause skin, eye and respiratory tract irritation. Avoid breathing dust and minimize contact with skin and eyes. Wear long sleeve shirts, long pants and eye protection. Always maintain adequate ventilation. Use a dust mask or NIOSH/MSHA approved respirator as appropriate in dusty or poorly ventilated areas.

**Handling Precautions**

Stack ToughRock Shaftliner panels flat on a level surface. As individual sheets are removed for installation, they should be raised carefully on edge and carried in a vertical position. Appropriate handling also is outlined in Gypsum Association Publications GA-216 and GA-801.

Take care to avoid impact, undue flexing and subsequent damage to board edges, ends and corners.

**Material Safety Data Sheet**

Material Safety Data Sheet (MSDS) is available upon request or online at [www.buildgp.com/safetyinfo](http://www.buildgp.com/safetyinfo).

*continued* →

**Submittal Approvals**

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Date \_\_\_\_\_

### Physical Properties

Properties	Toughrock® Shaftliner
Thickness, nominal inches <sup>3</sup>	1" (25.4 mm), ± 1/32" (0.8 mm)
Width, nominal <sup>3</sup>	24" (610 mm) – 3/32" (2.4 mm)
Length, standard <sup>3</sup>	8' (2440 mm) to 12' (3658 mm) ± 1/4" (6.4 mm)
Weight <sup>1</sup> , lbs./sq. ft., nominal (kg/m <sup>2</sup> )	4 (19.5)
Edges <sup>3</sup>	Double beveled
Surfacing	Recycled paper coverings on face, back and long edges
Flexural Strength <sup>3</sup> spacing, min.	
Parallel, lbf. (N)	77 (343)
Perpendicular, lbf. (N)	228 (1014)
Hardness, lbf. (N) (core, edges and ends)	≥15
Packaging	Single pieces
Surface Burning Characteristics <sup>4, 2</sup>	
Flame Spread	15
Smoke Developed	0

(The core is noncombustible when tested in accordance with ASTM E136.)

<sup>1</sup> Represents approximate weight for design and shipping purposes. Actual weight may vary depending on manufacturing location and other factors.

<sup>2</sup> Surface burning characteristics per ASTM E84.

<sup>3</sup> Specified minimum values are as defined in ASTM C1396.

<sup>4</sup> Products qualify for NFPA Class A or IBC Class 1.



U.S.A. Georgia-Pacific Gypsum LLC  
 Georgia-Pacific Gypsum II LLC  
 Canada Georgia-Pacific Canada LP

#### SALES INFORMATION AND ORDER PLACEMENT

U.S.A. West: **1-800-824-7503**  
 Midwest: **1-800-876-4746**  
 South Central: **1-800-231-6060**  
 Southeast: **1-800-327-2344**  
 Northeast: **1-800-947-4497**

CANADA Canada Toll Free: **1-800-387-6823**  
 Quebec Toll Free: **1-800-361-0486**

#### TECHNICAL INFORMATION

U.S.A. and Canada: **1-800-225-6119**, [www.gpgypsum.com](http://www.gpgypsum.com)

**TRADEMARKS** TOUGHROCK and the GEORGIA-PACIFIC logo are trademarks owned by or licensed to Georgia-Pacific Gypsum LLC.

**WARRANTIES, REMEDIES AND TERMS OF SALE** For current warranty information for this product, please go to [www.gpgypsum.com](http://www.gpgypsum.com) and select the product for warranty information. All sales of this product by Georgia-Pacific are subject to our Terms of Sale available at [www.gpgypsum.com](http://www.gpgypsum.com).

**UPDATES AND CURRENT INFORMATION** The information in this document may change without notice. Visit our website at [www.gpgypsum.com](http://www.gpgypsum.com) for updates and current information.

**CAUTION** For product fire, safety and use information, go to [www.buildgp.com/safetyinfo](http://www.buildgp.com/safetyinfo) or call 1-800-225-6119.

**FIRE SAFETY CAUTION** Passing a fire test in a controlled laboratory setting and/or certifying or labeling a product as having a one-hour, two-hour, or any other fire resistance or protection rating and, therefore, as acceptable for use in certain fire rated assemblies/systems, does not mean that either a particular assembly/system incorporating the product, or any given piece of the product itself, will necessarily provide one-hour fire resistance, two-hour fire resistance, or any other specified fire resistance or protection in an actual fire. In the event of an actual fire, you should immediately take any and all actions necessary for your safety and the safety of others without regard for any fire rating of any product or assembly/system.